

NKPZ2.E42816 Motor Controllers, Float- and Pressure-operated - Component

Page Bottom

Motor Controllers, Float- and Pressure-operated - Component

See General Information for Motor Controllers, Float- and Pressure-operated - Component

BARKSDALE INC E42816

3211 FRUITLAND AVE LOS ANGELES, CA 90058 USA

Float operated switches, Model(s) BLS followed by 270, 300, 500, 700, 750, 800, 810, 1700, 1750, 1775, 1800, 1900, 1950, 73100, 76607 or 77700 followed by B, BR, N, PP, PV, S or SS, followed by 01, 02, 03, 04, 05, 06, 07, 08, 9, 10, 11, 12, 21, 22, 23 or 99, followed by A24, B24, C24, D24, E24, F03, F24, JXX, TXX or SJXX, where XX is inches, followed by A, B, C, D, E, F, G, H, J, K, L, M, N, O, P, Q or S, followed by 1, 2, 4, 5, 7, 9 or 10, followed by 1, 2, 3, 4 or 5.; Models L followed by Series (007, 270, 300, 500, 700, 750, 800, 810, 1700, 1750, 1775, 1800, 1900, 1950, 73100, 76607 or 77700), followed by 0-999 or Q1-Q99. Engineering No's.

Pressure and vacuum operated switches, "Series 7000", Model(s) CD followed by 1S or 2S, followed by A, B, C, F, GH, H, J, K or M, followed by 2, 3, 18, 80 or 150, may be followed by SS, may be followed by P1-P10, may be followed by F3, B1-B10, Q1-Q99, S#, Z1 or W; Models CDPD followed by 1S or 2S, followed by A, B, C, F, GH, H, J, K or M, followed by 2, 3, 18, 80 or 150, may be followed by SS, may be followed by F3, B1-B10, Q1-Q99 or W; Models VCD followed by 1S or 2S, followed by A, B, C, F, GH, H, J, K or M, followed by P1-P10, may be followed by F3, B1-B10, Q1-Q99, S#, Z1 or W; Models VCDPD followed by 1S or 2S, followed by A, B, C, F, GH, H, J, K or M, followed by 2, 3, 18, 80 or 150, may be followed by A, B, C, F, GH, H, J, K or M, followed by 2, 3, 18, 80 or 150, may be followed by SS, may be followed by F3, B1-B10, Q1-Q99 or W.

Pressure operated switches, "Series 8000", Model(s) 8 followed by one number 0-4 or a letter A-D, F-H, followed by one number 1-6 or a letter A-F, followed by 1 or 2, followed by two letters and one number (PL1, PL2, PL5), might be followed by the letter B, V, N or E, might be followed by the suffixes, HD, VA, W or LH.

Pressure-operated switches, "Series 7000", Model(s) 7 followed by 1, 2 or 3, followed by 0 through 7, followed by S, F, P or B, followed by 1, 2, 3, 4, 5, 6, 7, 8, 9 or X, followed by 1 through 8, followed by 1 through 4, followed by B, V, N, E or D, followed by 1 through 3000, followed by R or F, or S001 through S9999, followed by Q1 through Q99, W01 throughW 999 or Z1..

Pressure-operated switches, Model(s) 96200 followed by BB, CC or GH, followed by -1, -2, -3, -4, -5 or -6, may be followed by SS, may be followed by -T1, -T2, -T3, or T6, may be followed by S#, Z1, Z12, Z17, W, P1-P10, 96201; Models 96201 followed by BB, CC or GH, followed by -1, -2, -3, -4, -5 or -6, may be followed by SS, may be followed by -T1, -T2, -T3, or T6, may be followed by S#, Z1, Z12, Z17, W, P1-P10; Models 96210 followed by BB, CC or GH, followed by -1, -2, -3, -4, -5 or -6, may be followed by SS, may be followed by -T1, -T2, -T3, or T6, may be followed by SB, CC or GH, followed by -T1, -T2, -T3, or T6, may be followed by SS, may be followed by -1, -2, -3, -4, -5 or -6, may be followed by SS, may be followed by -1, -2, -3, -4, -5 or -6, may be followed by S#, Z1, Z12, Z17, W, P1-P10; Models 96220 followed by SB, CC or GH, followed by -1, -2, -3, -4, -5 or -6, may be followed by SS, may be followed by -1, -2, -3, -4, -5 or -6, may be followed by SS, may be followed by -1, -2, -3, -4, -5 or -6, may be followed by SF, Z1, Z12, Z17, W, P1-P10, 96221; Models 96221 followed by SB, CC or GH, followed by -T1, -T2, -T3, or T6, may be followed by SB, CC or GH, followed by -T1, -T2, -T3, or T6, may be followed by SF, Z1, Z12, Z17, W, P1-P10; Models CMSPS followed by DD, EE, FF, JJ, LL, MM, NN or XX, followed by 05, 15 or 100, may be followed by -PL or -SS, may be followed by V, N or E, may be followed by -1, -2, -3, -4, -5 or -6, may be followed by SF, Z1, D2S-U, D2T-U; Models D3S followed by AA, A, B, C, E, F, H, or GH, followed by 2, 3, 18, 80 or 150, may be followed by SF, Z1, D2S-U, D2T-U; Models D3S followed by -PL or -SS, may be followed by V, N or E, may be followed by -PL or -SS, may be followed by SF, Z1, Models MSPS followed by -PL, E, FF, JJ, LL, MM, NN or XX, followed by 05, 15 or 100, may be followed by -PL or -SS, may be followed by SF, Z1, Models MSPS followed by -PL, -2, -3, -4, -5 or -6, may be followed by SF, Z1, Z12, Z17, W, P1-P10; Models T96211 followed by SF, Z1, Z12, Z17, W, P1-P10; Mode

Note - Models may be followed by additional numbers and suffixes.

Marking:	Company	name an	d model	designation.
Last Und	lated on 20	007-02-2	7	

Questions? Notice of Disclaimer Page Top

NKPZ.E42816 Motor Controllers, Float- and Pressure-Operated

Page Bottom

Motor Controllers, Float- and Pressure-Operated

See General Information for Motor Controllers, Float- and Pressure-Operated

BARKSDALE INC

E42816

3211 FRUITLAND AVE LOS ANGELES, CA 90058 USA

Enclosed type pressure operated switches, "Series 8000", Model(s) 8 followed by one number 1..4 or a letter A..G, followed by one number 1..6 or a letter A..F, followed by 1..8, followed by two letters and one number (CA3, CD1), maybe followed by the letter B, V, N, E, S maybe followed by the suffixes HD, VA, W or LH followed by the suffix UL..

Enclosed type, Pressure-operated switches, Model(s) FF-, followed by max. 4 numbers, followed by P (a), SW2000UL, UDS7UL.

Pressure and vacuum switches, Model(s) CD or VCD, followed by 1H or 2H, followed by A, B, C, F, H, GH, J, K or M, followed by 2, 3, 18, 80 or 150, may be followed by SS, B1-B10, F3, FX, P1-P10, Q1-Q99, S#, Z1 or W; Models CDPD or VCDPD, followed by 1H or 2H, followed by A, B, C, F, GH, H, J, K or M, followed by 3, 18, 80 or 150, may be followed by SS, F3, FX, B1-B10, P1-P10, Q1-Q99, S#, Z1 or W.

Pressure switches, Model(s) 9048, 9048S#; Models B1T, B2T, followed by A, B, C, E, F, GH, H, J, K, L, M, S, or X, followed by 12, 32, 48, 65, or 72 and may be followed by suffix FX, or P1-P10, or S#, or Q1-Q99, and suffix CS, C-9612, C-9612#S, C-9622, C-9622#S, T7, TC-9048, TC-9048S#, TC-9612, TC-9622, TC-9622#S, UDS3UL.

Pressure-operated switches, Model(s) 9617 followed by -3, -4, -5 or -6, may be followed by FX, S#, Z1; Models 9617, followed by -3, -4, -5 or -6, may be followed by FX, S# or Z1; Models 96200, T96201, 96201, T96221, P6221, 96210, 96211, 96220, 96221 followed by BB, CC or GH, followed by -1, -2, -3 -4, -5 or -6, may be followed by SS, followed by -T4, -T5 or -T6, may be followed by S#, Z1, Z12, W or P1-P10; Models D1H-, D2H-, D1T- followed by U and D3H-, followed by AA, A, B, C, E, F, H or GH, followed by 2, 3, 18, 80 or 150, may be followed by SS, B1-B10, FX, P1-P10, Q1-Q99, S#, Z1 or W; Models E1H with suffix letters B, F, GH, H, J, K, M or R, followed by suffix numbers 15, 20, 90, 250, 500 or VAC, with or without additional suffix letters S#, Z1 , N, T or V, with or without suffix U, with or without suffix -F2, FX, with or without suffix -BR, -PLS, -P6, S#, Z1 may be followed by Q1-Q99.

Pressure-operated switches: Enclosed, Model(s) PC1H, followed by 1, 2, 3, 4, 5, followed by N or blank, followed by HS or S#, followed by Q1 thru Q99; PD1H followed by 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, followed by N or blank, followed by HS or S#, followed by Q1 thru Q99..

(a) - Also represented by Order No. F 01370 followed by four numbers.

Note - All product may be followed by additional numbers and letters.

Last Updated on 2007-02-27

Questions?

Notice of Disclaimer

Page Top

Copyright © 2007 Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2007 Underwriters Laboratories Inc.®"